

INSTALLATION INSTRUCTIONS

Item#1331-923

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE (Fig.1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
3. Loosen screws (C) to remove mounting plate (A) from fixture body (D).
4. Attach mounting plate (A) to junction box (not included) with mounting screws (B) (Size: #8-32N*L0.6"). The side of the mounting plate (A) marked "GND" and two convex points must face out.


Fig. 1

Set#A-020-120SQA

-Mounting screw*2

-Ground screw

-Mounting plate




CONNECTING THE WIRES (Fig. 2)

5. Connect the electrical wires as shown in Fig. 2, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the mounting plate (A) using the green screw provided. After the wires are connected, tuck them carefully inside the junction box.

FINISHING THE INSTALLATION (Fig.1)

6. Place fixture body (D) over mounting plate (A) and secure with screws (C).
7. Screw the crystal ball assembly (F) onto the fixture body (D) and tighten it securely.
8. Install (1) one candelabra base bulb (K) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification — **DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**
9. Place the glass shade (L) over the socket and twist to secure it to the socket cup (J).

Fig. 2



Your installation is now complete. Return power and test the fixture.

