

INSTALLATION INSTRUCTIONS

Item#1336-923

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

ASSEMBLING THE FIXTURE (Fig. 1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clean area. Take care not to misplace any small parts necessary for installation.
3. Secure decorative assembly (G) onto all thread (H) on the fixture body.
4. Determine the desired hanging height and thread rods (F1, F2) to the all thread of the decorative assembly (G). Attach canopy (D) by screwing onto rod (F1). Carefully pass the wires through each rod during assembly.
5. Thread screws (A) into the pre-drilled holes in the circular strap (B) spaced the same distance apart as the holes in the canopy (D). The length of screws (A) may be adjusted if necessary.
6. Attach circular strap (B) to the junction box (not included) with mounting screws (C) (Size: #8-32N*L0.6"). The side of the circular strap (B) with "GND" marked on it and two convex points must face out.

CONNECTING THE WIRES (Fig. 2)

7. Connect the electrical wires as shown in fig 2, making sure that all wire connectors are secured. If your outlet has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the circular strap (B) using the green screw provided.
8. Tuck the wire connectors neatly into the ceiling junction box and then raise the canopy (D) to the ceiling.

COMPLETING THE INSTALLATION (Fig. 1)

9. Slide screws (A) through the canopy (D) and secure with finials (E).
10. Slide the plastic washer (M), metal tube (N), crystal ball (O), plastic washer (M) over the finial assembly (P), then screw the assembly into the light fixture and tighten firmly.
11. Install (6) six candelabra base bulbs (J) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification — **DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**
12. Place the glass shade (I) over the socket and twist to secure it to the socket cup (K).

The net weight of this fixture is over 4.5kgs, please ensure to remove all the glass shades before inspect branch circuit connections, this will help you to conveniently hold the fixture body.

Your installation is now complete. Return power to the junction box and test the fixture.

Fig. 1

Set# A-020
-Circular Strap
-Ground Screw
-Mounting Screw*2




Fig. 2

