

INSTALLATION INSTRUCTIONS

Item#2079-870/860 (New. 2025/07/02)

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE (Fig.1)

1. Shut off the power at the circuit breaker and remove the old fixture, including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clean area. Take care not to lose any small parts necessary for installation.
3. Thread canopy screws (B) into pre-drilled holes in mounting plate (A). Spaced same distance apart as holes in canopy (E), and secure with the nuts (D) provided. The length of canopy screws (B) may be adjusted if necessary.
4. Attached mounting plate (A) to outlet box (Not included) using mounting screws (C) (Size: #8-32N*L1"). The side of mounting plate (A) marked with "GND" must face out.
5. Thread stem (K) to the fixture (L), then install metal ring (J) onto the stem (K).
6. Determine the desired hanging height and thread rods (I & H) to nipple on top metal ring (J). Carefully feed wires through each rod as you assemble. Note: Remove the all thread, if installing with one 6" rod only.
7. Attach fixture canopy (E) by threading onto rod (H).
8. The support cable (F) is provided to support the weight of fixture while wiring. Align fixture to mounting plate (A) and attach hook on end of support cable (F) into a slot located on mounting plate (A). Carefully allow support cable (F) to support weight of fixture while wiring (Fig.1).

CONNECTING THE WIRES (Fig. 2)

9. Connect the electrical wires as shown in fig.2, making sure that all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to mounting plate (A) using the ground screw provided.
10. Tuck the wire connectors neatly into the outlet box.

FINISHING THE INSTALLATION (Fig.1)


11. Raise canopy (E) over canopy screws (B) and secure with cap nuts (G).
12. Install (9) nine candelabra base bulbs up to 60 watts or CFL or LED equivalent (not included) in accordance with the fixture specification. — **DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**
13. Hook ceramic pieces (A9,B9,C9,D9) to the second tier of the metal ring (J) in the order shown in the diagram cyclically.
14. Hook ceramic pieces (D9,C9,B9,A9) to the first tier of the metal ring (J) in the order shown in the diagram cyclically (Fig.1).

Your installation is now complete. Return power and test the fixture.

Fig. 1


Set# A-020-A
-Mounting Screw*2
-Ground Screw
-Mounting Plate

6" Rod# W35-H-870/860
12" Rod# W35-1-870/860



Candle Cover# CCV21048P-870 /860

Fig. 2



Note: Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

Replace swivel to be loop system (Fig.3)

1. Unscrew the nut (E4), then remove lock washer (E3), support cable (F), flat plate (E2) and swivel (E1) from the canopy (E).
2. Attach one loop (S) to other loop (S) by using quick link (T).
3. Place loop (S) over the canopy (E), then place flat plate (E2), support cable (F) and lock washer (E3) onto the protruding nipple at the top of loop (S), securing with hex nut (E4).

Fig.3

